


Dust Storm Impacts

on Human Mars Mission Equipment and Operations

1

Michelle Rucker
NASA Johnson Space Center
Mars Study Capability Team



EXPLORATION INTEGRATION AND SCIENCE DIRECTORATE



Mars Isn't Your Daddy's Surface Exploration Mission

2

- ❑ **Apollo spacecraft were one-time use, each landing at a different site**
 - NASA is looking at multiple missions to a single landing site
- ❑ **Apollo missions were about a week long**
 - Mars mission will start *at least* two years before the crew even launches from Earth, when cargo is pre-deployed to Mars
 - Mars surface equipment life may be 10+ years of active use
- ❑ **Apollo crews only ventured a few km from Lander**
 - NASA is looking at Mars surface scenarios where crews may take “camping trips” hundreds of kilometers from a landing site
- ❑ **Apollo didn't worry about forward contamination**
 - If we're searching for life on Mars, we have to be more careful



Surface Mission By the Numbers

*No firm decisions have been made
But this is the current thinking*

3

Multiple visits to a single landing site

Economics are better if we re-use assets, rather than abandon them

100 km

Notional crew excursion radius from landing zone

- Goal is to extend as far as possible
- Robotic assets may rove even further

~500

Days maximum surface stay for any given mission

- Driven by orbital mechanics
- Short (<30 day) stays have been considered, but don't save \$

Twenty Six

Months between mission opportunities

Conjunction class missions



Number of crew to the surface for any given mission

Studies have assessed 2 to 6 crew per mission



Here's What a Mars Campaign *Might* Look Like

4

FIRST we send cargo, including a surface power system



Power System +
Cargo

THEN we send an Ascent Vehicle and ISRU to fill its empty tanks



Ascent Vehicle +
Propellant
Manufacturing System

WHEN the tanks are full, crew lands and begins surface mission




Habitat + Crew
+ Logistics

SUBSEQUENT crews land at the same site and use existing infrastructure



Additional Crew
+ Ascent
Vehicles + Cargo



Impacts to Equipment

5



Surface Habitat

6

❑ Habitat is re-used for multiple long-duration expeditions

❑ Considerations

- Crew ingress/egress: open hatch alternative, dust-resistant pressure seals, locking mechanisms
- Cabin fans/filters to remove airborne dust in the cabin and portable vacuum cleaners to clear surface dust (+ power for both)
- Regenerative air/water system compatibility with chemicals in dust
- Ability to remove embedded dust from softoods
- Cleaning tools
- Clothing and cleaning rags: dispose or wash?
- Dust accumulation on windows, handrails, radiator panels

❑ In spite of best efforts, some dust is likely to migrate into the habitat





Surface Power Systems

7

- ❑ Solar Power is sensitive to accumulated *and* atmospheric dust
 - Robots can go dormant, but humans can't
- ❑ We can clean dusty solar arrays—but can't fix atmospheric dust
 - Over-size arrays and increase energy storage capacity to survive storm
 - Or develop alternatives, such as fission power
- ❑ Power cable connections between surface assets will be challenging
 - Need dust-resistant connectors
 - Some of these connections may be made by robots before the crew arrive





Robots Can Hibernate When Power Is Low

8

But humans have to breathe, eat, stay warm and get back home

Spirit Selfie on Sol 586

*Image courtesy of
Cornell University*



*Image courtesy of NASA/
JPL-Caltech/Cornell*



Dust Accumulation on Spirit's solar arrays reduced available power




Rovers

9

❑ Pressurized Crew Rovers are Mobile Habitats

- All the same concerns as a stationary habitat
- Accumulation can compromise even non-solar rovers (Apollo battery)
- Navigation optics
- Worst-case: solar-powered rover caught in lengthy, severe storm away from the habitat





EVA Spacesuits and Tools

EVA
Extravehicular
Activity

10

- ❑ **Biggest concern: How/where to perform routine maintenance on dusty spacesuits?**
- ❑ **Considerations:**
 - Crew ingress/egress dust mitigation
 - Seal and mechanism integrity
 - Managing dust accumulation on helmet visor, backpack, boots, gloves, thermal components
 - Abrasion damage to seals, visors, cameras
 - Dust embedded in softgoods, such as suit fabrics
 - EVA Tools: overheating, grit abrasion of mechanisms
- ❑ **May need to leave EVA suits on Mars unless cleaned to meet planetary protection guidelines**
 - Cost penalty to bring new suits with new crews
 - Alternative is to refurbish/resize old suits on Mars for new crews



*Apollo 17
Dusty EVA suit & Astronaut Cernan*



Notional Mars EVA Suit Soiling




Mars Ascent Vehicle

MAV
Mars Ascent
Vehicle

11

- ❑ MAV is the first leg of the crew's return to Earth
- ❑ Similar concerns as habitat
 - Airborne dust in the cabin, grit abrasion on seals and mechanisms, reduced window visibility or thermal system malfunction due to dust accumulation
- ❑ MAV is a key link in the planetary protection chain
 - If we can keep dust out of the MAV, we can keep Martian dust from migrating back to Earth
- ❑ Key to minimizing dust in MAV is to never expose cabin to Mars
 - One option is tunnel from a rover to the MAV





Impacts to Operations

12



Landing on Mars

13

- ❑ Storms along well-worn tracks may influence landing site selection
- ❑ Landing during a dust storm could make it difficult to detect and avoid hazards
 - Boulders, sand dunes, rovers, surface habitat
 - Mitigation might include advanced hazard detection and avoidance systems
- ❑ Lengthy storm could cut into schedule margins for critical surface operations, such as manufacturing propellant from Mars resources for crew departure
- ❑ Equipment sensitive to dust accumulation is equally affected by man-made dust storms produced by lander descent engines

Click below to play on-line video

Descent Engines Will Kick Up Dust

Morpheus Free Flight #10, NASA Kennedy Space Center

14

*Jump
to 2:15*

Engine dust plumes will have the added complication of unburned propellants or propellant byproducts mixed with the dust



Habitat Operations

15

- ☐ **Keeping dust out of the habitat is likely to involve special operational procedures**
 - May add time getting EVA crew back inside
 - Concern for emergency ingress
- ☐ **Housekeeping is likely to be time-consuming on Mars**
 - How will we clean the cleaning tools?
 - How much consumables mass will be devoted to cleaning, and will this mass have to be delivered from Earth?
- ☐ **Reduced visibility through habitat windows could disrupt telerobotic operations or science activities**



Rover Excursions

16

- ❑ **Reduced driving visibility and solar power availability could influence surface exploration planning**
 - Poor visibility makes driving treacherous
 - Crew rescue schemes, remote safe havens, better storm prediction, or surface navigation and hazard avoidance provisions
- ❑ **Special operational procedures could add time getting EVA crew back into the rover**
- ❑ **Housekeeping will be time-consuming**
- ❑ **Will need time and consumables to repair grit-damaged pressure seals and mechanisms**



EVA Operations

EVA

Extravehicular
Activity

17

- ❑ Clearing dust off of solar/radiator panels, windows, etc. could be time-consuming
 - Cuts into science operations time
- ❑ Ideally, equipment will be designed to shed dust, or will include autonomous dust clearing provisions
- ❑ Getting crew in/out of dusty suits may add time
 - Cuts into overall EVA time





MAV Ascent

MAV

Mars Ascent
Vehicle

18

- ❑ Like the lander's descent engines, the MAV's ascent engines will create a man-made dust storm
 - Lofted dust—potentially mixed with ascent propellants or residues
 - Settling on the habitat or rovers
- ❑ Ascent flight paths that avoid surface infrastructure overflight will be desirable
- ❑ Haven't identified any reason MAV can't launch in a dust storm
 - Visibility may make pre-launch preparations difficult




Click below to play on-line video

Ascent Engines Also Kick Up Dust

Morpheus Free Flight #7, NASA Kennedy Space Center

19





Key Take Aways

20

- ❑ Robotic missions have provided valuable insights into Martian dust storms
- ❑ Dust storms pose challenges for a human Mars mission
- ❑ NASA is actively considering ways to reduce the impact of dust storms
 - Robust equipment designs
 - Contingency operations planning



Questions?

21



References

22

- ❑ Wagner, S.A. (2006) *The Apollo Experience Lessons Learned for Constellation Lunar Dust Management*, NASA/TP-2006-213726.
- ❑ Landis, G.A., T.W. Kerslake, P.P. Jenkins, and D.A. Scheiman (2004), *Mars Solar Power*, NASA/TM-2004-213367.
- ❑ Strella, P.M., and Herman, J.A. (2010), *The Mars Surface Environment and Solar Array Performance*.
- ❑ Rucker, M.A., et al. (2016), *Solar Versus Fission Surface Power for Mars*, AIAA 2016-5452.
- ❑ Boyle, R.M., L. Rodriggs, C. Allton, M. Jennings, L. Aitchison (2013), *Suitport Feasibility - Human Pressurized Space Suit Donning Tests with the Marman Clamp and Pneumatic Flipper Suitport Concepts*.
- ❑ Rucker, M.A., S. Jefferies, A.S. Howe, R. Howard, N. Mary, J. Watson, and R. Lewis (2016), *Mars Surface Tunnel Element Concept*, IEEE 8.0204.
- ❑ Wang, H. and M.I. Richardson (2015), *The Origin, Evolution, and Trajectory of Large Dust Storms on Mars During Mars Years 24-30 (1999-2011)*, Icarus 251 (2015) 112-127.